





Oscillating Spindle Sander

• NEVER LEAVE SANDERS RUNNING UNATTENDED.
• ALWAYS MAINTAIN SECURE FOOTING AROUND THE SANDER.
• NEVER WEAR GLOVES, LOOSE CLOTHING, JEWELRY, NECKTIES, OR LONG LOOSE HAIR NEAR SANDERS.
• NEVER LEAN OVER OR REACH UNDER RUNNING SANDERS.
 NEVER POWER SAND METALS, INCLUDING NAILS, SCREWS, OR OTHER FASTENERS IN THE WOOD. (Sparks can ignite air borne sawdust. Countersink fasteners below wood surface before sanding)
• NEVER POWER SAND PAINTED WOOD OR OTHER MATERIALS IN THE DESIGN SHOP.
• ALWAYS RUN DUST COLLECTOR WHEN SANDING.
 Configuration: A cylindrical sanding spindle mounted in a table
 Configuration: A cylindrical sanding spindle mounted in a table Action: The spindle spins (and on some models oscillate up and down) while the wood is moved against the tabletop.
2. Action: The spindle spins (and on some models oscillate up and
 Action: The spindle spins (and on some models oscillate up and down) while the wood is moved against the tabletop. Adjustments: some models have interchangeable spindles of various
 Action: The spindle spins (and on some models oscillate up and down) while the wood is moved against the tabletop. Adjustments: some models have interchangeable spindles of various diameter

.....